




**LS2024H**

#### Performance & Dimensions

- Speed: 25-40km/h
- Range: 55-65kms
- Climbing Ability: up to 25%
- Min.Turning Radius: 3.5m
- Brake Distance: 4m
- Passenger Capacity: 2
- Loading Weight: 350kgs
- Net Weight: 520kgs
- Rear cargo box dimension: 770x1100x250mm
- Overall Dimension: 2670x1180x1890mm

#### Electric System

- Motor: 4KW DC, 3KW/4KW AC
- Battery: 6pcs, 8V140AH Lead Acid
- Charger: 48V/20A
- Controller: Curtis Brand
- Lights: Headlight, turning light, brake light, with 48V/12V converter



#### Body & Frame

- Welded Steel Frame with phosphating and e-coating treatment
- PP injected plastic front and rear body
- PP plastic roof
- Split front windshield
- Powder coated roof support
- 2-point seatbelt
- Comfortable wide seat and backrest
- Anti-slip floor mat
- PP injected dashboard
- Foldable side mirror

#### Steering, Brake & Suspension

- Single stage rack and pinion steering system with automatic rocker compensating function
- Rear wheel mechanical drum brake
- Front and rear plate spring + cylinder hydraulic shock absorber
- Rear axle two stage deceleration, motor direct drive
- 10x7 aluminum rim, 205/50-10 tyre

#### Optional Accessories

- Laminated windshield with wiper
- Wood grain dashboard, backrest and steering wheel
- Glove box door with lock
- Inner rear view mirror
- Weather Enclosure
- Solar Panel
- Onboard charger
- Right Hand Drive System
- 4-wheel hydraulic brake with hand park brake



**Suzhou Lexsong Electromechanical Equipment CO.,Ltd.**

Room 536 Ori Mansion, No.328 XingHu Street, Suzhou Industrial Park, China

sales@lexsong-ev.com, www.lexsong-ev.com, +86 137 7167 0476