



LS6062KF

Performance & Dimensions

- Speed: 25-30km/h
- Range: 60-70kms
- Climbing Ability: up to 20%
- Min.Turning Radius: 4m
- Brake Distance: 4m
- Passenger Capacity: 6
- Loading Weight: 500kgs
- Net Weight: 800kgs
- Overall Dimension: 3880x1490x1950mm

Electric System

- Motor: 5KW AC/DC
- Battery: 8pcs, 6V210AH Lead Acid
- Charger: 48V/25A
- Controller: Curtis Brand
- Digital Meters with speedometer, odometer
- Lights: Headlight, turning light, brake light, with 48V/12V converter

Body & Frame


- Welded Steel Frame with sand blasting and painting treatment
- PP injected plastic front and rear body
- 6 doors made by Aluminum
- Laminated front windshield and safety glass side window
- High-elastic imitation leather seat
- Anti-slip floor mat
- PP injected dashboard
- Foldable side mirror

Steering, Brake & Suspension

- Single stage rack and pinion steering system with automatic rocker compensating function
- 4 wheel hydraulic drum brake, with hand park brake
- Front MacPherson independent suspension
Rear integral shock damping suspension
- Rear axle two stage deceleration, motor direct drive
12" aluminum rim, 155R12C tyre

Optional Accessories

- Air Conditioner
- Seatbelt (2-point or 3-point)



Suzhou Lexsong Electromechanical Equipment CO.,Ltd.

Room 536 Ori Mansion, No.328 XingHu Street, Suzhou Industrial Park, China

sales@lexsong-ev.com, www.lexsong-ev.com, +86 137 7167 0476