



LS9020KF

Performance & Dimensions

- Speed: 40km/h
- Range: 90-100kms
- Climbing Ability: up to 20%
- Min. Turning Radius: 3.8m
- Brake Distance: 5m
- Passenger Capacity: 2
- Loading Weight: 210kgs
- Net Weight: 560kgs
- Overall Dimension: 2050x1380x1620mm

Electric System

- Motor: 4KW AC
- Battery: 5pcs, 12V120AH Lead Acid
- Charger: 60V/20A
- Controller: Curtis Brand
- Lights: Headlight, turning light, brake light, with 60V/12V converter

Body & Frame


- Welded Steel Frame with phosphating and e-coating treatment
- PP injected plastic front and rear body
- 2 doors made by steel frame with plastic cover sheet
- Laminated front windshield and safety glass side window
- 3-point seatbelt
- High-elastic imitation leather seat
- Anti-slip floor mat
- PP injected dashboard
- Foldable side mirror
- Rear Storage Trunk

Steering, Brake & Suspension

- Single stage rack and pinion steering system with automatic rocker compensating function
- 4 wheel hydraulic disc brake, with hand park brake
- Front MacPherson independent suspension
- Rear integral shock damping suspension
- Rear axle two stage deceleration, motor direct drive
- 12' aluminum rim, 145/70R12 tyre

Optional Accessories

- Air Conditioner



Suzhou Lexsong Electromechanical Equipment CO.,Ltd.

Room 536 Ori Mansion, No.328 XingHu Street, Suzhou Industrial Park, China

sales@lexsong-ev.com, www.lexsong-ev.com, +86 137 7167 0476